



## Lightweight clay masonry mortar

### Item No. 05.022, 05.222, 10.122

DIN 18946

- Mortar for lightweight clay bricks
- Structurally adapted
- For timber-frame masonry



Masonry mortar for lightweight clay bricks used for timber-frame infills and interior shells. The wood-chip component allows adaptation to the material composition of the lightweight clay bricks, with the density and physical properties also being adjusted in this way. The bagged material (dry mortar) never expires.

For technical consulting service teams  
and sales see [www.claytec.de/en](http://www.claytec.de/en)  
Product data and application  
see reverse

GERMANY  
Claytec GmbH & Co. KG  
Nettetalter Straße 113-117,  
41751 Viersen  
Phone: +49 2153 918-0  
[www.claytec.de/en](http://www.claytec.de/en)

## Lightweight clay masonry mortar

### Item No. 05.022, 05.222, 10.122

#### Clay masonry mortar - DIN 18946 - LMM 0/4 f - M0 - 1,4

**Area of application** masonry mortar for clay bricks and lightweight clay bricks in the application class I or II. Not to be used as plastering mortar or as the base material for the manufacture of plastering mortar.

**Composition** Natural construction clay up to 5 mm, sand 0-2 mm, wood granulate (chips) up to 20 mm.  
Grain classification, oversize grain according to DIN 0/4, < 8 mm.

**Material parameters** Drying shrinkage < 3.0 %. Strength class M0. Gross density class 1.4. Thermal conductivity 0.59 W/m·K.  $\mu$ -value 5/10. Building material class B2\*.

Building material class, B2 respectively, better classification is possible subject to fire protection tests (Lehmbau Regeln DVL 2009, p. 97).

#### Supply form, coverage

Earth-moist 5.022 in 1.0 T big-bags (yields 700 l masonry mortar)

Earth-moist 05.222 in 0.5 T big-bags (yields 350 l masonry mortar)

Dry 10.122 in 25 kg bags (yields 20.5 l masonry mortar), 48 bag/Pal.

**Storage** Store in a dry place. Earth-moist lightweight clay masonry mortar should be applied no later than 3 months after manufacture, in the case of dry goods, unlimited storage is possible. **Earth-moist goods must be stored in winter protected from freezing, otherwise workability during freezing is impaired.**

**Required material** depending on the brick format and wall thickness the following amount of mortar litre/m<sup>2</sup> is produced

Brick format	11.5cm	17.5cm	24.0cm	36.0cm
DF	29	-	(uncommon)	(uncommon)
NF	27	-	65	101
2DF	20	-	50	80
3DF	-	29	42	(uncommon)

**Mortar preparation** Add approx. 10% water (earth-moist) or approx. 30-35% (dry) using any rotary drum, pan and trough mixers. For smaller amounts use a motor whisk or mix by hand.

**Processing** The mortar is processed according to the rules of masonry. If lime plaster is planned, strip the masonry joints to an even level, to improve plaster adhesion later scrap them out sharply to create a recess of max. 3 mm.

**Working time** Since no chemical setting process takes place, the material can be processed over several days if kept covered. It can remain in mortar pumps and hoses for just as long.

**Colour** The colour of the mortar may deviate from the colour of the clay bricks and lightweight clay bricks.